

LED Waterproof Fittings

Introducing our IP65 Ingress Protection Waterproof tubes, built dust-tight allowing it to resist rain and jets of water.



Product Features

- Luminous efficacy up to 120lm/W and 80lm/W
- Easy to install
- IP65, free from water and dirt
- Without opening the lampshade for direct wiring
- Perfect replacement for the whole set of T8 fluorescent lighting fixture
- Save up to 80% in electricity consumption compared to fluorescent lighting fixture

Applications

Widely used for Domestic and Commercial Lighting, Offices, Supermarkets, Shops, Hotels & similar environment

NEW

2 LED TUBES
INCLUDED

120CM x 2 - Fitting

BOX QTY.
10IP65
RATED

2 x 18W VT-12023

6387 - 4000K Day White

6399 - 6400K White

EAN Code

3800157625036

3800157626385

A+

Watts:	2 x 18W	On/Off:	>15000
Voltage/Frequency:	AC:200-240V, 50/60Hz	Life span:	20,000 Hours
Luminous Flux:	3400lm	Body Type:	ABS+PC
LED Type:	SMD	IP Rating:	IP65
CRI:	>80	Dimension:	1260 x 112 x 63mm
PF:	>0.9	Gross weight:	1330 g
Beam Angle:	120°		

NEW

2 LED TUBES
INCLUDED

150CM x 2 - Fitting

BOX QTY.
10IP65
RATED

2 x 22W VT-15022

6388 - 4000K Day White

6400 - 6400K White

EAN Code

3800157625043

3800157626392

A+

Watts:	2 x 22W	On/Off:	>15000
Voltage/Frequency:	AC:200-240V,50/60Hz	Life span:	20,000 Hours
Luminous Flux:	4000lm	Body Type:	ABS+PC
LED Type:	SMD	IP Rating:	IP65
CRI:	>80	Dimension:	1560 x 112 x 63mm
PF:	>0.9	Gross weight:	1650 g
Beam Angle:	120°		

NEW



120CM - Fitting

36W VT-1238

6395 - 4000K Day White
6396 - 6400K White

EAN Code

3800157625999
3800157626002

BOX QTY.

20

A+



IP65
RATED

Watts:	36W	PF:	>0.6	On/Off:	>10000
Voltage/Frequency:	AC:200-240V, 50/60Hz	Beam Angle:	120°	Life span:	30,000 Hours
Luminous Flux:	3200lm	Body Type:	PC	Gross weight:	350 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1260 x 43 x 23mm		

NEW



150CM - Fitting

45W VT-1545

6397 - 4000K Day White
6398 - 6400K White


EAN Code

3800157626019
3800157626026

BOX QTY.

20

A+



IP65
RATED

Watts:	45W	PF:	>0.6	On/Off:	>10000
Voltage/Frequency:	AC:200-240V, 50/60Hz	Beam Angle:	120°	Life span:	30,000 Hours
Luminous Flux:	4100lm	Body Type:	PC	Gross weight:	390 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1560 x 43 x 23mm		



60CM - Fitting


18W VT-6076

6283 - 4000K Day White
6282 - 6400K White

BOX QTY.
 12

EAN Code

3800157616478
3800157616461



Watts:	18W	PF:	>0.5	On/Off:	>10000
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	1440lm	Body Type:	ABS+PC	Gross weight:	560 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	600 x 65 x 58mm		



120CM - Fitting


36W VT-1249

6285 - 4000K Day White
6284 - 6400K White

BOX QTY.
 12

EAN Code

3800157616492
3800157616485



Watts:	36W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	2880lm	Body Type:	ABS+PC	Gross weight:	916 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1200 x 65 x 58mm		



150CM - Fitting


48W VT-1574

6287 - 4000K Day White
6286 - 6400K White

BOX QTY.
 12

EAN Code

3800157616515
3800157616508



Watts:	48W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	3840lm	Body Type:	ABS+PC	Gross weight:	1150 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1500 x 65 x 58mm		



60CM - Fitting

18W VT-6048


6198 - 4500K Day White
6199 - 6000K White

EAN Code

3800157603256
3800157603263

BOX QTY. **12**

A+



IP65
RATED

Watts:	18W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	1400lm	Body Type:	Plastic	Gross weight:	800 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	600 x 76 x 66 mm		



120CM - Fitting

36W VT-1248


6200 - 4500K Day White
6201 - 6000K White

EAN Code

3800157603270
3800157603287

BOX QTY. **12**

A+



IP65
RATED

Watts:	36W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	2880lm	Body Type:	Plastic	Gross weight:	1450 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1200 x 76 x 66mm		



150CM - Fitting

48W VT-1548


6184 - 4500K Day White
6185 - 6000K White

EAN Code

3800157602389
3800157602396

BOX QTY. **12**

A+



IP65
RATED

Watts:	48W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	3920lm	Body Type:	Plastic	Gross weight:	1800 g
LED Type:	SMD	Dimension:	IP65		
CRI:	>70	Instant start :	1480 x 76 x 66mm		



120CM - Fitting

60W VT-1260 SMD

6179 - 4000K Day White
6062 - 6000K White

EAN Code

3800157601610
3800230625212

BOX QTY.


09

A++

120⁺⁺
LM/W
HIGH LUMENS

IP65
RATED

Watts:	60W	PF:	> 0.9	On/Off:	>10000
Voltage/Frequency:	AC: 200-240V, 50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	7200lm	Body Type:	Plastic + Aluminium	Gross weight:	2100 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1200 x 86 x 70mm		



150CM - Fitting

70W VT-1573

6266 - 4000K Day White
6267 - 6000K White

EAN Code

3800157612586
3800157612593

BOX QTY.

06

A++

120⁺⁺
LM/W
HIGH LUMENS

IP65
RATED

Watts:	70W	PF:	> 0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V, 50/60Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	8400lm	Body Type:	Plastic + Aluminium	Gross weight:	2750 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1500x 86 x70mm		

