

# LED Display Screen

VTAC LED's Display screen series perfectly designed for the best video output and display of images and information. Offering Display color of 281 trillions(synchronized). The perfect product for advertising and marketing.

## Product Features

- Powerful LED display screen available in Indoor and Outdoor series
- Displays digital content such as Video, Images & Information
- Good Brand Value addition for Advertising
- Easy Installation

## Applications


Suitable for Outdoor and Indoor Advertising, Hotel conference room, Restaurants, Showrooms, Casinos, Government facilities, Theaters, Retail outlets, Traffic control room, Security monitoring room, Stage background, HD cinema, Shopping malls, Railway stations, Airports.



## Indoor Display Screen

**P3 Indoor LED Display Screen**

SKU: 11109 3800157644686

 Box Qty.  
**6 Pcs**


Pixel pitch	3mm	Brightness	≥1100 CD/M2
Panel size	L192xH192xT13mm	Working environment temperature	-10 to +40°C
Physical density	111111/M2	Working environment humidity	10%~70% RH
Pixel configuration	1,1,1(R,G,B)	Display working voltage	AC46~4HZ,220V±15%/110V±15%
Driving method	1/16 Constant current	Color temperature	8500K-11500K
LED Chip Type	SMD2121	Gray scale/color	≥16.7M color
Display resolution	4096(64x64)dots	Input signal	RF\ S-Video\ RGB etc
Module weight	0.35Kg	Control system	PCTV nonlinearity card, DVI Display card, Linsn control system
Module port	HUB75-B	Mean free error time	>5000 Hours
Module working voltage	5VDC	Life Hours	100000 Hours
Power	30W	Steel box weight	40 Kg/M2
Viewing angle	120 Degrees	Steel box size	L576Xh768x80mm
Option distance	3-45M		
Driving device	5020		
Every square metre module	27.13 PCS		
Maximum power	1000 W/M2		
Frame Frequency	60Hz		
Refresh frequency	400-800 Hz/S		



Indoor Display Screen

**P4 Indoor LED Display Screen**

SKU: 11079 3800157619493

Box Qty.  
**6 Pcs**



- Plug & Play
- Ideal For Renting Purpose
- Portable Moving For Events

### Screen Parameter

Pixel Density	62500dots/sqm
Brightness	1100nits
Optimum View Distance	more than 5m
Gray Scale	16bits
Display Color	281 trillions(synchronized)
Operation Power	AC 220V-240V/ 50/60Hz
Power Consumption	300W/cabinet
Control Mode	Synchronized
Refresh Frequency	400-700HZ
Support Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	UTP140M,SINGLE MODE FIBER 15KM
Life Span(50% Brightness)	100000hrs
IP(Front)	IP40
Control System	PCTV nonlinearity card, DVI display card Linsn control system

### LED Cabinet Parameter

Cabinet Size(L*h*d)	512*512*85mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	2*4=8
Power Consumption	300w/cabinet
Cabinet Material	Iron
Cabinet Weight	8kg/cabine

### LED Module Parameter

Pixel Pitch	4mm
Led Specification	SMD2121
Led Configuration	SMD 3 in 1
Module Size	256*128mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106
Power Consumption	25-30W



## Indoor Display Screen

**P5 Indoor LED Finished Cabinet**
 Box Qty.  
**6 Pcs**

SKU: 11077 3800157617468

## Screen Parameter

Pixel Density:	40000dots/sqm
Brightness:	1800nits
Optimum View Distance:	more than 5m
Gray Scale:	16bits
Display Color:	281 trillions(synchronized)
Operation Power:	220V-240V
Max Power Consumption:	750W/sqm
Control Mode:	Synchronized
Refresh Frequency:	400-700HZ
Fram Frequency:	60HZ
Support Signal Input:	S-Video,RGBHV,YUV etc.
Control Distance:	UTP140M,SINGLE MODE FIBER 15KM
Life Span(50% Brightness):	100000hrs
IP(Front/rear):	IP20

## LED Cabinet Parameter

Cabinet Size(L*h*d):	640*640mm
Cabinet Resolution:	128*128
Module Quantity Each Cabinet:	2*4=8
Average Power Consumption:	300w/cabinet
Cabinet Material:	Iron
Cabinet Size:	8kg/cabinet

## LED Module Parameter

Pixel Pitch:	5mm
Led Specification:	SMD3528
Led Configuration:	SMD 3 in 1
Module Size:	320*160mm
Module Resolution:	64*32=2048dot
Drive Method:	1/16 scan constant current
Drive IC:	SM16106

 Windows 10
**COM700-MEDIA PLAYER**

SKU: 11088 3800157622820

## LED Display Player with Industrial PC

One TS802 sending card inside
Dual Display - Supports Max 1280*800
Supports SD Memory Card/USB/HDMI Out/Internet
USB and SD Card Memory Playing
Compact and Easy to Install
7" Touch Screen with windows 10 Inside
Size - 320*180*50mm
Input - AC:120-260V
1 x Audio In
1 x Audio Out
1 x DVI In
1 x HDMI Out
4 USB Interface

Sending Box  Box Qty.  
**20 Pcs**

SKU: 500082

Sending Card  Box Qty.  
**20 Pcs**

SKU: 500081





Outdoor Display Screen

**P6 Outdoor LED Finished Cabinet** Box Qty. **6 Pcs**

SKU: 11078 3800157617475



### Screen Parameter

Pixel Density	27777dots/sqm
Brightness	6500nits
Optimum View Distance	more than 6m
Gray Scale	16bits
Display Color	281 Trillions(synchronized)
Operation Power	220V-240V
Max Power Consumption	1350W/sqm
Control Mode	Synchronized
Refresh Frequency	400-800HZ
Fram Frequency	60HZ
Support Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	Utp140m, Single Mode Fiber 15km
Operating Humidity	10%-90%
Life Span(50% Brightness)	100000hrs
IP(Front/rear)	IP65/IP45

### LED Cabinet Parameter

Cabinet Size(L*h*d)	768*768mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	4*4=16
Average Power Consumption	800w/cabinet
Cabinet Material	Iron
Cabinet Size	25kg/cabinet

### LED Module Parameter

Pixel Pitch	6mm
Led Specification	SMD3535
Led Configuration	SMD 3 in 1
Module Size	192*192mm
Module Resolution	32*32=1024dot
Drive Method	1/8 scan constant current
Drive IC	SM16106