


INSTALLATION INSTRUCTION

Model: VT-1172

LED STEP/WALL LIGHT OUTDOOR



INTRODUCTION

Thank you for selecting and buying V-TAC LED STEP/WALL LIGHT OUTDOOR. V-TAC will serve you the best. Please read these instructions carefully before starting the installation and keep this manual handy for future reference. If you have any other query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best.

TECHNICAL PARAMETERS

	lamp	warm white	natural white	cool white	
		lumen (lm)	190 lm	200 lm	210 lm
performance parameter	color temperature (K)	3000K	4000K	6400K	
	CRI	≥80			
	type of LED	SMD LED			
	beam angle	90			
	decay rate (%)	less than 3% within 1000 working hours			
	total power (W)	3-4W			
	lifespan (hrs)	≥30000hrs			
	high voltage testing	1750Vac/1min			
	LED parameter	lighting efficiency	100Lm/W		
		chip quantity	10PCS		
series-parallel way		5C2B			
voltage		43-47V			
current		50mA			
driver parameter	input parameter	100~240VAC, 50/60Hz			
	power factor	0.5			
	output parameter	50mA 40-90v			
structure parameter	material	PC			
	dimension	151X72X154mm			
	cut-out	/			
	protection class	I级			
environment parameter	IP	IP65			
	application	hotel, home-lighting, recreation place, supermarket, office building			
	operating temperature	-25℃ ~ 50℃, 10% ~ 90% R.H.			
packing specification	storage temperature	-30℃ ~ 85℃, 0% ~ 95% R.H.			
	Qty/Ctn	carton size	N.W	G.W	