

**PRODUCT INTRODUCTION**

This panel lighting fixture is with LED diode, has advanced technology, energy savings and environmental protection, long life span, saving electricity cost and almost no maintenance time and cost needed. It has 100% efficiency and brighter than any other old fixtures.

**PRODUCT OVERVIEW**

No maintenance, easy to install, high efficiency, low electricity, power saving, long life span, low temperature and no glare.

**APPLICATION USAGE**

The LED Panel light can be used in hotels, offices, factories, conferences, meeting rooms, commercial complexes, residential buildings, schools, colleges, universities, hospitals, etc.

**TECHNICAL PARAMETERS**

Model No:	VT-10001	VT-20001	VT-30001	VT-10002	VT-20002	VT-30002
Power:	10W	20W	30W	10W	20W	30W
Direct Connect Voltage:	24-48V	54-100w	25-45W	24-48V	54-100V	25-45V
Lumens:	750lm	1600lm	2400lm	700lm	1400lm	2100lm
Beam Angle:	120°	120°	120°	120°	120°	120°
CRI:	80	80	80	80	80	80
Protection Rating:	20	20	20	20	20	20
Operating Temperature:	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C
Unit size:	160*45*65mm	Ø290*45*65mm	Ø430*45*65mm	160*45*72mm	290*45*72mm	430*45*72mm
Cut size:	Ø138*32mm	Ø170*32mm	Ø405*32mm	Ø138*32mm	Ø170*32mm	Ø405*32mm

**INSTALLATION REQUIREMENTS**

- Install only by certified electrician.
- Please connect with the driver properly before connecting main supply.
- Proper grounding should be ensured throughout installation.
- The lighting should be located in dry areas.

**INSTALLATION INSTRUCTION**

