



# CE LVD TEST REPORT

For

LED LINEAR LIGHTS

Model No.: VT-10001, VT-20001, VT-30001, VT-10002, VT-20002, VT-30002

Applicant : V-TAC EXPORTS LIMITED  
ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD  
CENTRAL, CENTRAL, HONGKONG

Manufacturer : V-TAC EXPORTS LIMITED  
ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD  
CENTRAL, CENTRAL, HONGKONG

Issued By : Global-Standard Testing Service Co., Ltd.  
Room 1911, 1914, Noble Plaza, Qian Jin 1st Road, Bao An  
district, Shenzhen, Guangdong, China.

Tel : +86 755 33863599

Email : [Market@gstslab.com](mailto:Market@gstslab.com)



Report Number : A01.06.0230S

Issued Date : August 08, 2017

Date of Report : August 08, 2017

**Note:**

1. The test data and result is based on the tested sample only.
2. Please verify information in the report on GST web: [www.gstslab.com](http://www.gstslab.com) through report number.
3. All rights reserve, the pirate edition investigates necessarily! This report shall not be reproduced unless under the authority of Global-Standard Testing Service Co., Ltd.

<b>EN60598-1</b> <b>Luminaires—Part 1 :General requirements and tests</b> <b>EN60598-2-2</b> <b>Part 2-2:Particular requirements</b> <b>Section Two – Recessed luminaires</b>	
Report reference No. ....:	A01.06.0230S
Testing laboratory .....	Global-Standard Testing Service Co., Ltd.
Location.....:	Room 1911-1914, Noble Plaza, Qian Jin 1st Road, Bao An district, Shenzhen, Guangdong, China.
Applicant.....:	V-TAC EXPORTS LIMITED
Address:.....:	ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD CENTRAL, CENTRAL, HONGKONG
Manufacturer.....:	V-TAC EXPORTS LIMITED
Address:.....:	ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD CENTRAL, CENTRAL, HONGKONG
Standards.....:	EN 60598-1:2015 EN 60598-2-2:2012 EN 62031:2008+A1:2013+A2:2015 EN 61347-1:2015 EN 61347-2-13:2014 EN 62471:2008 EN 62493:2015
Procedure deviation.....:	N/A
Non-standard test method.....:	N/A
Type of test equipment .....	LED LINEAR LIGHTS
Trademark .....	
Model/Type designation.....:	VT-10001, VT-20001, VT-30001, VT-10002, VT-20002, VT-30002
Rating.....:	AC 85-265V, 50/60Hz, 20W Max
Copyright blank test report:	Global-Standard Testing Service Co., Ltd.
Test item particulars:	--
Operating Condition	Continuous
Tested for IT power systems	No
IT testing, phase-phase voltage (V)	N/A.
Class of equipment	Class II equipment
Protection against ingress of water	IP20

Possible test case verdicts :  
test case does not apply to the test object N(/A.)  
test object does meet the requirement P(ass)  
test object does not meet the requirement F(ail)

Name and address of the testing laboratory :

Global-Standard Testing Service Co., Ltd.  
Room 1911-1914, Noble Plaza, Qian Jin 1st Road, Bao An District, Shenzhen, Guangdong, China.

**Tested by** : Justin Li August 01, 2017  
Signature Date

Justin Li / Engineer  
Name/title

**Reviewed by** : Jerry Hu August 08, 2017  
Signature Date

Jerry Hu / Supervisor  
Name/title

**Approved by** : Tim Sun August 08, 2017  
Signature Date

Tim Sun / Manager  
Name/title

<p><b>General remarks:</b></p>	
<p>Clause number between brackets refer to clauses in IEC 60598-1</p> <p>"(see remark #)" refers to a remark appended to the report.</p> <p>"(see appended table)" refers to a table appended to the report.</p> <p>Throughout this report a comma is used as the decimal separator.</p> <p>The test results presented in this report relate only to the object tested.</p> <p>This report shall not be reproduced except in full without the written approval of the testing laboratory.</p> <p>Unless otherwise specified, test are made under normal conditions at an ambient temperature within the range of 15°C to 35°C, RH45% to 75% and an air pressure of 860mbar of 1060mbar</p>	<p>Attachment with:</p> <p>1) Photo documentation</p>
<p>Brief description of the test sample:</p> <ol style="list-style-type: none"> <li>1.This report covers the LED LINEAR LIGHTS with models VT-10001, VT-20001, VT-30001, VT-10002, VT-20002, VT-30002 for indoor use;</li> <li>2.All models have the same construction except for LED number and wattage;</li> <li>3.The model VT-20001 was selected as representative sample to perform all testing;</li> <li>4.The standard of LED modules for general lighting was evaluated with reference to EN 62031;</li> <li>5.The standard EN 62471 and EN 62493 have been considered with positive result in this report;</li> <li>6.LED LINEAR LIGHTS were supplied by SELV isolated electrical control gear. Live parts of control gear and lamp enclosure were separated by double or reinforce insulation, which was evaluated under EN 61347-2-13 &amp; EN61347-1.</li> </ol>	

## Label

### Representative



### Note:

1. Due to similarity of the labels, only above label was listed;
2. All models have the same marking plate except the model name and input rating with wattage;
3. The height of WEEE directive mark is at least 7mm, and others directive mark are at least 5mm.

**EN 60598-2-2**

Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
--------	------------------------------	-----------------	---------

<b>2.3 (0)</b>	<b>GENERAL TEST REQUIREMENTS</b>		P
2.3 (0.1)	Information for luminaire design considered..... :	Standard Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
2.3 (0.3)	More sections applicable..... :	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—

<b>2.4 (2)</b>	<b>CLASSIFICATION</b>		P
2.5 (2.2)	Type of protection .....	Class II	—
2.5 (2.3)	Degree of protection .....	IP20	—
2.5 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces..... :	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—
2.5 (2.5)	Luminaire for normal use .....	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
	Luminaire for rough service .....	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—

<b>2.6 (3)</b>	<b>MARKING</b>		P
2.6 (3.2)	Mandatory markings		P
	Position of the marking	On the body	P
	Format of symbols/text		P
2.6 (3.3)	Additional information		P
	Language of instructions	English	N/A
2.6 (3.3.1)	Combination luminaires		N/A
2.6 (3.3.2)	Nominal frequency in Hz	50/60Hz	P
2.6 (3.3.3)	Operating temperature		N/A
2.6 (3.3.4)	Symbol or warning notice	See marking	P
2.6 (3.3.5)	Wiring diagram		N/A
2.6 (3.3.6)	Special conditions		N/A
2.6 (3.3.7)	Metal halide lamp luminaire – warning		N/A
2.6 (3.3.8)	Limitation for semi-luminaires		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.6 (3.3.9)	Power factor and supply current		P
2.6 (3.3.10)	Suitability for use indoors		P
2.6 (3.3.11)	Luminaires with remote control		N/A
2.6 (3.3.12)	Clip-mounted luminaire – warning		P
2.6 (3.3.13)	Specifications of protective shields		N/A
2.6 (3.3.14)	Symbol for nature of supply		P
2.6 (3.3.15)	Rated current of socket outlet		N/A
2.6 (3.3.16)	Rough service luminaire		N/A
2.6 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments	Type Y	P
2.6 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
2.6 (3.3.19)	Protective conductor current in instruction if applicable		N/A
2.6 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		P
2.6 (3.3.21)	Non replaceable and non-user replaceable light sources information provided		P
	Cautionary symbol		P
2.6 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
2.6 (3.4)	Test with water	Legible	P
	Test with hexane	Legible	P
	Legible after test	Yes	P
	Label attached	Yes	P

<b>2.7 (4)</b>	<b>CONSTRUCTION</b>		<b>P</b>
2.7 (4.2)	Components replaceable without difficulty		P
2.7 (4.3)	Wireways smooth and free from sharp edges		P
<b>2.7 (4.4)</b>	<b>Lampholders</b>		<b>N/A</b>

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.7 (4.4.1)	Integral lampholder		N/A
2.7 (4.4.2)	Wiring connection		N/A
2.7 (4.4.3)	Lampholder for end-to-end mounting		N/A
2.7 (4.4.4)	Positioning		N/A
	- pressure test (N) .....		—
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N) .....		—
	After test the lampholder have not moved from its position and show no permanent deformation		N/A
2.7 (4.4.5)	Peak pulse voltage		N/A
2.7 (4.4.6)	Centre contact		N/A
2.7 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
2.7 (4.4.8)	Lamp connectors		N/A
2.7 (4.4.9)	Caps and bases correctly used		N/A
2.7 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
<b>2.7 (4.5)</b>	<b>Starter holders</b>		N/A
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A
<b>2.7 (4.6)</b>	<b>Terminal blocks</b>		P
	Tails		P
	Unsecured blocks		P
<b>2.7 (4.7)</b>	<b>Terminals and supply connections</b>		N/A
2.7 (4.7.1)	Contact to metal parts		N/A



EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.7 (4.7.2)	Test 8 mm live conductor		N/A
	Test 8 mm earth conductor		N/A
2.7 (4.7.3)	Terminals for supply conductors		P
2.7 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.8.2		N/A
	- electrical test according to 15.9		N/A
	- heat test according to 15.9.2.3 and 15.9.2.4		N/A
2.7 (4.7.4)	Terminals other than supply connection		N/A
2.7 (4.7.5)	Heat-resistant wiring/sleeves		N/A
2.7 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
<b>2.7 (4.8)</b>	<b>Switches</b>		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
<b>2.7 (4.9)</b>	<b>Insulating lining and sleeves</b>		P
2.7 (4.9.1)	Retainment		P
	Method of fixing..... :		—
2.7 (4.9.2)	Insulated linings and sleeves:		P
	Resistant to a temperature > 20 °C to the wire temperature or		P
	a) & c) Insulation resistance and electric strength		P

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	b) Ageing test. Temperature (°C)..... :		P
<b>2.7 (4.10)</b>	<b>Double or reinforced insulation</b>		<b>P</b>
2.7 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		P
	Safe installation fixed luminaires		P
	Capacitors and switches		N/A
	Interference suppression capacitors according to IEC 60384-14		N/A
2.7 (4.10.2)	Assembly gaps:		
	- not coincidental		N/A
	- no straight access with test probe		N/A
2.7 (4.10.3)	Retention of insulation:		P
	- fixed		P
	- unable to be replaced; luminaire inoperative		N/A
	- sleeves retained in position		N/A
	- lining in lampholder		N/A
<b>2.7 (4.11)</b>	<b>Electrical connections and current-carrying parts</b>		<b>P</b>
2.7 (4.11.1)	Contact pressure		P
2.7 (4.11.2)	Screws:		P
	- self-tapping screws		N/A
	- thread-cutting screws		P
2.7 (4.11.3)	Screw locking:		P
	- spring washer		N/A
	- rivets		P
2.7 (4.11.4)	Material of current-carrying parts		P
2.7 (4.11.5)	No contact to wood or mounting surface		N/A
2.7 (4.11.6)	Electro-mechanical contact systems		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
<b>2.7 (4.12)</b>	<b>Screws and connections (mechanical) and glands</b>		N/A
2.7 (4.12.1)	Screws not made of soft metal		N/A
	Screws of insulating material		N/A
	Torque test: torque (Nm); part .....		N/A
	Torque test: torque (Nm); part .....		N/A
	Torque test: torque (Nm); part .....		N/A
2.7 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
2.7 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm) .....		N/A
	- lampholder; torque (Nm) .....		N/A
	- push-button switches; torque 0,8 Nm .....		N/A
2.7 (4.12.5)	Screwed glands; force (Nm) .....		N/A
<b>2.7 (4.13)</b>	<b>Mechanical strength</b>		<b>P</b>
2.7 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm) .....		N/A
	- other parts; energy (Nm) .....	0.35Nm	P
	1) live parts		P
	2) linings		N/A
	3) protection		P
	4) covers		N/A
2.7 (4.13.3)	Straight test finger	30N	P
2.7 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.7 (4.13.6)	Tumbling barrel		N/A
<b>2.7 (4.14)</b>	<b>Suspensions, fixings and means of adjusting</b>		<b>P</b>
2.7 (4.14.1)	Mechanical load:		P
	A) four times the weight	0.420 X 4=1.68kg	P
	B) torque 2,5 Nm		N/A
	C) bracket arm; bending moment (Nm) .....		N/A
	D) load track-mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm) .....		N/A
	Metal rod. diameter (mm) .....		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
2.7 (4.14.2)	Load to flexible cables		N/A
	Mass (kg) .....		—
	Stress in conductors (N/mm <sup>2</sup> ) .....		N/A
	Mass (kg) of semi-luminaire .....		—
	Bending moment (Nm) of semi-luminaire .....		N/A
2.7 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles .....		N/A
	- strands broken .....		N/A
	- electric strength test afterwards		N/A
2.7 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
2.7 (4.14.5)	Guide pulleys		N/A
2.7 (4.14.6)	Strain on socket-outlets		N/A
<b>2.7 (4.15)</b>	<b>Flammable materials</b>		<b>P</b>
	- glow-wire test 650°C.....	See Test Table 2.16 (13.3.2)	P
	- spacing ≥30 mm		N/A
	- screen withstanding test of 13.3.1		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	- screen dimensions		N/A
	- no fiercely burning material		N/A
	- thermal protection		N/A
	- electronic circuits exempted		N/A
2.7 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A
<b>2.7 (4.16)</b>	<b>Luminaires for mounting on normally flammable surfaces</b>		N/A
	No lamp control gear..... :	(compliance with Section 12)	N/A
2.7 (4.16.1)	Lamp control gear spacing:		N/A
	- spacing 35 mm		N/A
	- spacing 10 mm		N/A
2.7 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
2.7 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
<b>2.7 (4.17)</b>	<b>Drain holes</b>		N/A
	Clearance at least 5 mm		N/A
<b>2.7 (4.18)</b>	<b>Resistance to corrosion</b>		<b>P</b>
2.7 (4.18.1)	- rust-resistance		P
2.7 (4.18.2)	- season cracking in copper		N/A
2.7 (4.18.3)	- corrosion of aluminium		N/A
2.7 (4.19)	Igniters compatible with ballast		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.7 (4.20)	Rough service vibration		N/A
<b>2.7 (4.21)</b>	<b>Protective shield</b>		N/A
2.7 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
2.7 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
2.7 (4.21.3)	No direct path		N/A
2.7 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment ..... :	See Test Table 2.16 (13.3.2)	N/A
2.7 (4.22)	Attachments to lamps not cause overheating or damage		N/A
2.7 (4.23)	Semi-luminaires comply Class II		N/A
<b>2.7 (4.24)</b>	<b>Photobiological hazards</b>		P
2.7 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		P
2.7 (4.24.2)	Retinal blue light hazard		P
	Luminaires with $E_{thr}$ :		P
	a) Fixed luminaires		P
	- distance x m, borderline between RG1 and RG2.. :		P
	- marking and instruction according 3.2.23		P
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
<b>2.7 (4.25)</b>	<b>Mechanical hazard</b>		P
	No sharp point or edges		P
<b>2.7 (4.26)</b>	<b>Short-circuit protection</b>		P

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.7 (4.26.1)	Adequate means of uninsulated accessible SELV parts		P
2.7 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
<b>2.7 (4.27)</b>	<b>Terminal blocks with integrated screwless earthing contacts</b>		N/A
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Voltage drop test, resistance < 0,05 Ω		N/A
<b>2.7 (4.28)</b>	<b>Fixing of thermal sensing control</b>		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material (°C)..... :		—
	100 cycles between t min and t max		N/A
	Temperature sensing control still in position		N/A
<b>2.7 (4.29)</b>	<b>Luminaires with non-replaceable light source</b>		<b>P</b>
	Not possible to replace light source		P
	Live part not accessible after parts have been opened by hand or tools		P
<b>2.7 (4.30)</b>	<b>Luminaires with non-user replaceable light source</b>		N/A
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N/A
	Minimum two fixing means		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
<b>2.7 (4.31)</b>	<b>Insulation between circuits</b>		N/A
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
<b>2.7 (4.31.1)</b>	<b>SELV circuits</b>		P
	Used SELV source		P
	Voltage ≤ ELV		P
	Insulating of SELV circuits from LV supply		P
	Insulating of SELV circuits from other non SELV circuits		N/A
	Insulating of SELV circuits from FELV		N/A
	Insulating of SELV circuits from other SELV circuits		N/A
	SELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
<b>2.7 (4.31.2)</b>	<b>FELV circuits</b>		N/A
	Used FELV source		N/A
	Voltage ≤ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets does not have protective conductor contact		N/A



**EN 60598-2-2**

Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.7 (4.31.3)	Other circuits		N/A
	Other circuits insulated from accessible parts according Table X.1		N/A
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3 of above		N/A
	- conductive part not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
<b>2.7 (4.32)</b>	<b>Overvoltage protective devices</b>		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A

<b>2.8 (11)</b>	<b>CREEPAGE DISTANCES AND CLEARANCES</b>		<b>P</b>
2.8 (11.2)	Creepage distances and clearances .....	See Table 1.7 (11.2)	P
	Working voltage (V) .....	AC 85-265V	—
	Rated pulse voltage (kV).....		—
	Voltage form.....	Sinusoidal <input checked="" type="checkbox"/> Non-sinusoidal <input type="checkbox"/>	—
	PTI.....	< 600 <input checked="" type="checkbox"/> ≥ 600 <input type="checkbox"/>	—
	Impulse withstand category (Normal category II) (Category III Annex U)	Category II <input checked="" type="checkbox"/> Category III <input type="checkbox"/>	—

<b>2.9 (7)</b>	<b>PROVISION FOR EARTHING</b>		<b>N/A</b>
2.9 (7.2.1 + 7.2.3)	Accessible metal parts		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	Metal parts in contact with supporting surface		N/A
	Resistance < 0,5 Ω .....		N/A
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a grove		N/A
	Earth makes contact first		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		N/A
2.9 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		N/A
2.9 (7.2.4)	Locking of clamping means		N/A
	Compliance with 4.7.3		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
2.9 (7.2.5)	Earth terminal integral part of connector socket		N/A
2.9 (7.2.6)	Earth terminal adjacent to mains terminals		N/A
2.9 (7.2.7)	Electrolytic corrosion of the earth terminal		N/A
2.9 (7.2.8)	Material of earth terminal		N/A
	Contact surface bare metal		N/A
2.9 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
2.9 (7.2.11)	Earthing core coloured green-yellow		N/A
	Length of earth conductor		N/A
<b>2.10 (14)</b>	<b>SCREW TERMINALS</b>		N/A
	Separately approved; component list .....	(see Annex 1)	N/A
	Part of the luminaire .....	(see Annex 3)	N/A

**EN 60598-2-2**

Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
--------	------------------------------	-----------------	---------

<b>2.10 (15)</b>	<b>SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS</b>		N/A
	Separately approved; component list .....	(see Annex 1)	N/A
	Part of the luminaire .....	(see Annex 4)	N/A

<b>2.11 (5)</b>	<b>EXTERNAL AND INTERNAL WIRING</b>		P
<b>2.11 (5.2)</b>	<b>Supply connection and external wiring</b>		<b>P</b>
2.11 (5.2.1)	Means of connection.....		N/A
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV $\leq 25$ V a.c./60 V d.c. or protected from outdoor environment		N/A
2.11 (5.2.2)	Type of cable .....		N/A
	Nominal cross-sectional area (mm <sup>2</sup> ).....	0.5 mm <sup>2</sup>	P
	Cables equal to IEC 60227 or IEC 60245		P
2.11 (5.2.3)	Type of attachment, X, Y or Z	Type Y	N/A
2.11 (5.2.5)	Type Z not connected to screws		N/A
2.11 (5.2.6)	Cable entries:		P
	- suitable for introduction		P
	- adequate degree of protection		P
2.11 (5.2.7)	Cable entries through rigid material have rounded edges		P
2.11 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
2.11 (5.2.9)	Locking of screwed bushings		N/A
2.11 (5.2.10)	Cord anchorage:		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	- covering protected from abrasion		N/A
	- clear how to be effective		N/A
	- no mechanical or thermal stress		N/A
	- no tying of cables into knots etc.		N/A
	- insulating material or lining		N/A
2.11 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A
	Glands not used as anchorage		N/A
	Labyrinth type anchorages		N/A
2.11 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		P
2.11 (5.2.10.3)	Tests:		N/A
	- impossible to push cable; unsafe		N/A
	- pull test: 25 times; pull (N) .....		N/A
	- torque test: torque (Nm).....		N/A
	- displacement ≤ 2 mm		N/A
	- no movement of conductors		N/A
	- no damage of cable or cord		N/A
	- function independent of electrical connection		N/A
2.11 (5.2.11)	External wiring passing into luminaire		P
2.11 (5.2.12)	Looping-in terminals		N/A
2.11 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.11 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
2.11 (5.2.16)	Appliance inlets (IEC 60320)		P
	Installation couplers (IEC 61535)		N/A
	Other appliance inlet or connector according relevant IEC standard		N/A
2.11 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
2.11 (5.2.18)	Used plug in accordance with		N/A
	- IEC 60083		N/A
	- other standard		N/A
<b>2.11 (5.3)</b>	<b>Internal wiring</b>		<b>P</b>
2.11 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		P
	- not delivered/ mounting instruction		P
	- factory assembled		P
	- socket outlet loaded (A)..... :		N/A
	- temperatures..... :	(see Annex 2)	P
	Green-yellow for earth only		N/A
2.11 (5.3.1.1)	Internal wiring connected directly to fixed wiring		P
	Cross-sectional area (mm <sup>2</sup> ) ..... :	0.4 mm <sup>2</sup>	P
	Insulation thickness	0.5mm	P
	Extra insulation added where necessary		N/A
2.11 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		P
	Adequate cross-sectional area and insulation thickness		P
2.11 (5.3.1.3)	Double or reinforced insulation for class II		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
2.11 (5.3.1.4)	Conductors without insulation		N/A
2.11 (5.3.1.5)	SELV current-carrying parts		P
2.11 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
2.11 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		P
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		P
	No twisting over 360°		P
2.11 (5.3.3)	Insulating bushings:		P
	- suitable fixed		P
	- material in bushings		P
	- material not likely to deteriorate		P
	- cables with protective sheath		N/A
2.11 (5.3.4)	Joints and junctions effectively insulated		N/A
2.11 (5.3.5)	Strain on internal wiring		N/A
2.11 (5.3.6)	Wire carriers		N/A
2.11 (5.3.7)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A

<b>2.12 (8)</b>	<b>PROTECTION AGAINST ELECTRIC SHOCK</b>		<b>P</b>
2.12 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		N/A
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		N/A
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
2.12 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N/A
2.12 (8.2.3.a)	Class II luminaire:		P
	- basic insulated metal parts not accessible during starter or lamp replacement		N/A
	- basic insulation not accessible other than during starter or lamp replacement		N/A
	- glass protective shields not used as supplementary insulation		N/A
2.12 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N/A
2.12 (8.2.3.c)	SELV circuits with exposed current carrying parts:		P
	Ordinary luminaire:		P
	- touch current .....		P
	- no-load voltage .....		N/A
	- other than ordinary luminaire:		N/A
	- nominal voltage .....	AC 85-265V	P
2.12 (8.2.4)	Portable luminaire have protection independent of supporting surface		N/A
2.12 (8.2.5)	Compliance with the standard test finger or relevant probe		N/A
2.12 (8.2.6)	Covers reliably secured		P
2.12 (8.2.7)	Discharging of capacitors $\geq 0,5 \mu\text{F}$		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	Portable plug connected luminaire with capacitor		N/A
	Other plug connected luminaire with capacitor		N/A
	Discharge device on or within capacitor		N/A
	Discharge device mounted separately		N/A

<b>2.13 (12)</b>	<b>ENDURANCE TEST AND THERMAL TEST</b>		P
2.13.1 (-)	If IP > IP 20 relevant test of (12.4), (12.5) and (12.6) after (9.2) before (9.3) specified in 4.13		—
2.13 (12.3)	Endurance test:		P
	- mounting-position .....	Normal use	—
	- test temperature (°C) .....	35°C	—
	- total duration (h).....	240h	—
	- supply voltage: Un factor; calculated voltage (V) ..	265	—
	- lamp used .....	LED lamp	—
2.13 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		
	- marking legible		P
	- no cracks, deformation etc.		P
2.13 (12.4)	Thermal test (normal operation)		P
2.13 (12.5)	Thermal test (abnormal operation)		P
2.13 (12.6)	Thermal test (failed lamp control gear condition):		N/A
2.13 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A) .....		—
	- case of abnormal conditions .....		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un ....		—
	- measured mounting surface temperature (°C) at 1,1 Un.....		N/A



EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	- calculated mounting surface temperature (°C) ..... :		N/A
	- track-mounted luminaires		N/A
2.13 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions..... :		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C)..... :		N/A
	- track-mounted luminaires		N/A
2.13 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
2.13 (12.7.1)	Luminaire without temperature sensing control		N/A
2.13 (12.7.1.1 )	Luminaire with fluorescent lamp ≤ 70W		N/A
	Test method 12.7.1.1 or Annex W ..... :		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions..... :		—
	- Ballast failure at supply voltage (V) ..... :		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions..... :		—
	- measured winding temperature (°C): at 1,1 Un..... :		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un..... :		—
	- calculated temperature of fixing point/exposed part (°C)..... :		—
	Ball-pressure test..... :	See Table 2.16 (13.2.1)	N/A
2.13 (12.7.1.2 )	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N/A
	- case of abnormal conditions..... :		—
	- measured winding temperature (°C): at 1,1 Un..... :		—

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un .....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Table 2.16 (13.2.1)	N/A
2.13 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N/A
	- case of abnormal conditions .....		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
2.13 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link .....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- manual reset cut-out.....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- auto reset cut-out.....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- case of abnormal conditions .....		—
	- highest measured temperature of fixing point/ exposed part (°C):.....		—
	Ball-pressure test: .....	See Table 2.16 (13.2.1)	N/A
2.13.1 (-)	Wiring, for connection to the supply, not reach unsafe temperature		N/A
	- measured temperature of the cable (°C) .....		N/A

<b>2.14 (9)</b>	<b>RESISTANCE TO DUST, SOLID OBJECTS AND MOISTURE</b>		<b>P</b>
2.14 (-)	If IP > IP 20 the order of tests as specified in clause 2.12		P
2.14 (9.2)	Tests for ingress of dust, solid objects and moisture:		—
	- classification according to IP .....	IP20	—
	- mounting position during test.....		—
	- fixing screws tightened; torque (Nm).....		—
	- tests according to clauses .....		—
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		P
	b) no talcum in dust-tight luminaire		P

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	d) i) For luminaires without drain holes – no water entry		N/A
	d) ii) For luminaires with drain holes – no hazardous water entry		N/A
	e) no water in watertight luminaire		N/A
	f) no contact with live parts (IP 2X)		P
	f) no entry into enclosure (IP 3X and IP 4X)		N/A
	f) no contact with live parts (IP3X and IP4X)		N/A
	g) no trace of water on part of lamp requiring protection from splashing water		N/A
	h) no damage of protective shield or glass envelope		
2.14 (9.3)	Humidity test 48 h	25°C, 93%RH, 48h	P

2.15 (10) INSULATION RESISTANCE AND ELECTRIC STRENGTH			P
2.15 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm .....		—
	Insulation resistance (MΩ) .....		—
	SELV		P
	- between current-carrying parts of different polarity:	100 MΩ	P
	- between current-carrying parts and mounting surface .....	100 MΩ	P
	- between current-carrying parts and metal parts of the luminaire .....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....		N/A
	- Insulation bushings as described in Section 5 .....		N/A
	Other than SELV		N/A
	- between live parts of different polarity .....		N/A
	- between live parts and mounting surface .....		N/A
	- between live parts and metal parts .....		N/A

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	- between live parts of different polarity through action of a switch .....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....		N/A
	- Insulation bushings as described in Section 5 .....		P
2.15 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test	No ignitor	P
	Luminaires with manual ignitors	No manual ignitor	N/A
	Test voltage (V).....		P
	SELV		P
	- between current-carrying parts of different polarity :	1500V	P
	- between current-carrying parts and mounting surface .....	1500V	P
	- between current-carrying parts and metal parts of the luminaire .....	1500V	P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....		N/A
	- Insulation bushings as described in Section 5 .....		N/A
	Other than SELV		N/A
	- between live parts of different polarity .....		N/A
	- between live parts and mounting surface.....		N/A
	- between live parts and metal parts.....		N/A
	- between live parts of different polarity through action of a switch .....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....		N/A
	- Insulation bushings as described in Section 5 .....		N/A
2.15 (10.3)	Touch current or protective conductor current (mA) :	<0.009mA	P

<b>2.16 (13)</b>	<b>RESISTANCE TO HEAT, FIRE AND TRACKING</b>		<b>P</b>
2.16 (13.2.1)	Ball-pressure test .....	See Test Table 2.16 (13.2.1)	P

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict

2.16 (13.3.1)	Needle-flame test (10 s)..... :	See Test Table 2.16 (13.3.1)	P
2.16 (13.3.2)	Glow-wire test (650°C)..... :	See Test Table 2.16 (13.3.2)	P
2.16 (13.4)	Proof tracking test (IEC 60112) ..... :	See Test Table 2.16 (13.4)	N/A

2.8(11.2)	TABLE: Clearance And Creep age Distance Measurements						P
Table 11.1	Minimum distances (mm) for a.c. (50/60 Hz) sinusoidal voltages						P
clearance cl and creep age distance decry at/of:	Up (V)	U rams. (V)	Required cl (mm)	cl (mm)	required decry (mm)	decry (mm)	
L and N on PCB	--	240	1.5	3.27	2.5	3.27	
Different polarity of fuse	--	240	1.5	4.52	2.5	4.52	
Live parts of driver PCB and accessible part	--	240	3.0	>3.0	5.0	>5.0	
Primary circuit and secondary circuit of LED driver PCB	--	240	3.0	>3.0	5.0	>5.0	
Primary winding of transformer and secondary circuit of LED driver	--	240	3.0	>3.0	5.0	>5.0	
<b>Supplementary information:</b>							

2.16 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics				P
Allowed impression diameter (mm) ..... :					—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)		
Diffuser	--	125°C	1.13<2.0mm		
LED PCB	--	125°C	0.65<2.0mm		
--	--	--	--		
<b>Supplementary information:</b>					

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict

2.16 (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)				P
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Diffuser	--	--	Yes	10	No flame
--	--	--	--	--	--
Supplementary information:					

2.16 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				P
Glow wire temperature .....		650°C		—	
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Diffuser	--	--	Yes	30	No flame
LED PCB	--	--	Yes	30	No flame
Any flame or glowing of the sample extinguished within 30 s of withdrawing the glow-wire, and any burning or molten drop did not ignite the underlying parts (Yes/No) .....					
Supplementary information:					

2.16 (13.4)	TABLE: Proof tracking test (IEC 60112)				N/A
Test voltage PTI .....				—	
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:					

EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict

ANNEX 1 错误! 未指定书签。 List of critical components and materials				
Component	manufacturers / trademark	Type / model	Value / rating	Approval/ Reference
Enclosure	Chang Chun Plastic Co., Ltd	FBT-756	V-0, 90°C	UL
Power supply cord	Various	1015	VW-1, 105°C, 22AWG	VDE
Internal wire	Various	1015	VW-1, 105°C, 24AWG	VDE
LED PCB	Heshan Dongli Electronic Technologies Co Ltd	EPA-M2	V-0, 130°C,	UL
Diffuser	Chang Chun Plastic Co., Ltd	FBT-756	V-0, 90°C	UL
LED	V-TAC EXPORTS LIMITED	2835	Vf: 2.5-3.8V; If 80mA CCT: 2500-6500K; view angle: 120	Test with appliance
Terminal block	Various	Various	V-1, 90°C	Test with appliance
LED driver	V-TAC EXPORTS LIMITED	V-series	Input:AC 85-265V, 50/60Hz, 0.5A; Output:DC 18-42V, 1A	CE

ANNEX 2	TABLE: Temperature measurements, thermal tests of Section 12		P
	Type reference .....	VT-20001	—
	Lamp used .....	LED	—
	Lamp control gear used .....	Independed LED Driver	—
	Mounting position of luminaire .....	As in normal use	—
	Supply wattage (W).....	19.2W	—
	Supply current (A) .....	0.13A	—
	Calculated power factor .....	--	—
	Table: measured temperatures corrected for ta = 25 °C:		N/A
	- abnormal operating mode.....		—
	- test 1: rated voltage .....	AC 265V	—

**EN 60598-2-2**

Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage..... :		—
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage ..... :		—
	- test 4: 1,1 times rated voltage or 1,05 times rated wattage..... :		—
	Through wiring or looping-in wiring loaded by a current of A during the test ..... :		—

**Temperature measurements, (°C)**

Part	Ambient	Clause 12.4 – normal				Clause 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Input wire for LED driver	--	38.5			105		
Tc for LED driver	--	53.6			75		
Input wire for LED	--	52.7			105		
Terminal block	--	29.5			90		
Diffuser, inside	--	51.3			90		
LED	--	74.6			Ref		
LED PCB	--	64.7			130		
Metal enclosure	--	30.3			75		
Mounting surface	--	30.3			90		
Amibent	--	25.0			25-30		

Supplementary information:

<b>ANNEX 3</b>	<b>Screw terminals (part of the luminaire)</b>	N/A
<b>(14)</b>	<b>SCREW TERMINALS</b>	N/A
(14.2)	Type of terminal ..... :	—
	Rated current (A) ..... :	—
(14.3.2.1)	One or more conductors	N/A
(14.3.2.2)	Special preparation	N/A
(14.3.2.3)	Terminal size	N/A
	Cross-sectional area (mm <sup>2</sup> ) ..... :	—
(14.3.3)	Conductor space (mm) ..... :	N/A



**EN 60598-2-2**

Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread)..... :		N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm)..... :		N/A
	Torque (Nm)..... :		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N)..... :		N/A
(14.4.8)	Without undue damage		N/A

<b>ANNEX 4</b>	<b>Screwless terminals (part of the luminaire)</b>		N/A
<b>(15)</b>	<b>SCREWLESS TERMINALS</b>		N/A
(15.2)	Type of terminal .....		—
	Rated current (A) .....		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5.1)	Terminals internal wiring		N/A
(15.5.1.1)	Pull test spring-type terminals (4 N, 4 samples)..... :		N/A

**EN 60598-2-2**


Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict
(15.5.1.2)	Pull test pin or tab terminals (4 N, 4 samples)..... :		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples) ..... :		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples) ..... :		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples) ..... :		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples)..... :		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples)..... :		N/A
(15.6)	Terminals external wiring		N/A
	Terminal size and rating		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N) ..... :		N/A
	Pull test pin or tab terminals (4 samples); pull (N) ..... :		N/A


EN 60598-2-2			
Clause	Requirement 错误! 未找到引用源。 Test	Result – Remark	Verdict


(15.6.3.1)	TABLE: Contact resistance test										N/A
	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											N/A
	Voltage drop of two inseparable joints										N/A
	Voltage drop after 10th alt. 25th cycle										N/A
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											N/A
	Voltage drop after 50th alt. 100th cycle										N/A
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											N/A
	Continued ageing: voltage drop after 10th alt. 25th cycle										N/A
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											N/A
	Continued ageing: voltage drop after 50th alt. 100th cycle										N/A
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											N/A
											N/A
Supplementary information:											


**Appendix 1**


Photo Documentation

<p>Photo 1</p> <p>View:</p> <p><input checked="" type="checkbox"/> Front</p> <p><input type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input type="checkbox"/> Internal</p>	
--	---

<p>Photo 2</p> <p>View:</p> <p><input type="checkbox"/> Front</p> <p><input checked="" type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input type="checkbox"/> Internal</p>	
--	--

<p>Photo 3</p> <p>View:</p> <p><input type="checkbox"/> Front</p> <p><input type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input checked="" type="checkbox"/> Internal</p>	
--	---

<p>Photo 4</p> <p>View:</p> <p><input type="checkbox"/> Front</p> <p><input type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input checked="" type="checkbox"/> Internal</p>	
--	--

<p>Photo 5</p> <p>View:</p> <p><input type="checkbox"/> Front</p> <p><input type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input checked="" type="checkbox"/> Internal</p>	
--	---

--END.--